

BURTON[®] WIRE & CABLE

MANUFACTURER OF QUALITY WIRE & CABLE

MULTI-CONDUCTOR UNSHIELDED CMP CABLES

No. of Conductors	Gauge Size	Stranding	Insulation Thickness	Jacket Thickness	Nominal OD
2	22	7 Strand	.008	.015	.122
3	22	7 Strand	.008	.015	.129
4	22	7 Strand	.008	.015	.141
5	22	7 Strand	.008	.015	.154
6	22	7 Strand	.008	.015	.168
8	22	7 Strand	.008	.015	.182
10	22	7 Strand	.008	.015	.214
12	22	7 Strand	.008	.015	.221
2	20	7 Strand	.008	.015	.134
3	20	7 Strand	.008	.015	.143
4	20	7 Strand	.008	.015	.156
6	20	7 Strand	.008	.015	.187
2	18	7 Strand	.009	.015	.157
3	18	7 Strand	.009	.015	.167
4	18	7 Strand	.009	.015	.184
6	18	7 Strand	.009	.015	.221
8	18	7 Strand	.009	.015	.241
2	16	26 Strand	.010	.015	.190
3	16	26 Strand	.010	.015	.202
4	16	26 Strand	.010	.015	.223

Construction :
Stranded bare
copper conductors
insulated with color
coded Plenum
Rated PVC, jacketed
with Plenum Rated
White PVC. Cables
are twisted prior to
jacketing. UL Rated
CL3P/FPLP

COLOR CODE: Black, Red, White, Green, Orange, Blue, Brown, Yellow, Purple, Gray, Pink, Tan.
Above cables also available as pairs or triads.

AWG #22, 20, 18, 16 Multiple Conductors

(UL) Standard 444, NEC Article 800



504 Silver Street Manchester, NH 03103
Phone (603) 624-2427 Fax (603) 641-9296