



MANUFACTURER OF QUALITY WIRE & CABLE

**MULTI-CONDUCTOR  
SHIELDED CMP CABLES**



No. of Conductors	Gauge Size	Stranding	Insulation Thickness	Jacket Thickness	Nominal OD
2	22	7 Strand	.008	.015	.127
3	22	7 Strand	.008	.015	.134
4	22	7 Strand	.008	.015	.146
5	22	7 Strand	.008	.015	.158
6	22	7 Strand	.008	.015	.175
8	22	7 Strand	.008	.015	.187
10	22	7 Strand	.008	.015	.220
12	22	7 Strand	.008	.015	.227
2	20	7 Strand	.008	.015	.138
3	20	7 Strand	.008	.015	.149
4	20	7 Strand	.008	.015	.162
6	20	7 Strand	.008	.015	.193
2	18	7 Strand	.009	.015	.163
3	18	7 Strand	.009	.015	.173
4	18	7 Strand	.009	.015	.188
6	18	7 Strand	.009	.015	.227
8	18	7 Strand	.009	.015	.246
2	16	19 Strand	.010	.015	.196
3	16	19 Strand	.010	.015	.208
4	16	19 Strand	.010	.015	.230

**Construction :** Stranded bare copper conductors insulated with color coded 75°C Plenum Rated PVC, jacketed with Plenum Rated White PVC. Cables are twisted prior to jacketing. All cables are available with an overall aluminum / polyester shield and stranded tinned copper drain wire. UL Rated CL3P/FPLP

COLOR CODE: Black, Red, White, Green, Orange, Blue, Brown, Yellow, Purple, Gray, Pink, Tan.  
Above cables also available as pairs or triads.

AWG #22, 20, 18, 16 Multiple Conductors

(UL) Standard 444, NEC Article 800



**504 Silver Street Manchester, NH 03103  
Phone (603) 624-2427 Fax (603) 641-9296**