



MULTI-CONDUCTOR SHIELDED CL3R CABLES

Gauge Size	No. of Conductors	Stranding	Insulation Thickness	Jacket Thickness	Nominal O.D.
12	2	65	.012	.020	.286
14	4	19	.012	.018	.260
14	2	19	.010	.018	.220
16	2	19	.010	.015	.230
16	3	26	.010	.015	.197
16	2	26	.010	.015	.197
18	12	7	.009	.015	.306
18	10	7	.009	.015	.293
18	8	7	.009	.015	.247
18	6	7	.009	.015	.226
18	4	7	.009	.015	.190
18	3	7	.009	.015	.170
18	2	7	.009	.015	.163
20	12	7	.008	.015	.250
20	10	7	.008	.015	.240
20	8	7	.008	.015	.207
20	6	7	.008	.015	.190
20	4	7	.008	.015	.160
20	3	7	.008	.015	.145
20	2	7	.008	.015	.138
22	16	7	.008	.015	.246
22	12	7	.008	.015	.230
22	10	7	.008	.015	.215
22	8	7	.008	.015	.184
22	6	7	.008	.015	.170
22	5	7	.008	.015	.155
22	4	7	.008	.015	.141
22	3	7	.008	.015	.130
22	2	7	.008	.015	.124

Construction:

Stranded bare copper conductors insulated with color PVC, jacketed with Gray PVC. Cables are twisted prior to jacketing. All cables are available with an overall aluminum/polyester shield and a stranded tinned copper drain wire.



COLOR CODE: Black, Red, White, Green, Orange, Blue, Brown, Yellow, Purple, Gray, Pink, Tan, Light Green, Light Blue, Light Orange, Light Purple

Above cables are also available as pairs or triads; unshielded, overall shielded, each group shielded.