



<i>Gauge Size</i>	<i>No. of Conductors</i>	<i>Stranding</i>	<i>Insulation Thickness</i>	<i>Jacket Thickness</i>	<i>Nominal O.D.</i>
12	2	65/30	.012	.020	.286
14	4	19/0147	.010	.018	.260
14	2	19/0147	.010	.018	.220
16	4	26/30	.010	.015	.230
16	3	26/30	.010	.015	.215
16	2	26/30	.010	.015	.197
18	12	7/0152	.009	.015	.306
18	10	7/0152	.009	.015	.293
18	8	7/0152	.009	.015	.247
18	6	7/0152	.009	.015	.226
18	4	7/0152	.009	.015	.190
18	3	7/0152	.009	.015	.170
18	2	7/0152	.009	.015	.163
20	12	7/0121	.008	.015	.250
20	10	7/0121	.008	.015	.240
20	8	7/0121	.008	.015	.207
20	6	7/0121	.008	.015	.190
20	4	7/0121	.008	.015	.160
20	3	7/0121	.008	.015	.145
20	2	7/0121	.008	.015	.138
22	16	7/0096	.008	.015	.246
22	12	7/0096	.008	.015	.230
22	10	7/0096	.008	.015	.215
22	8	7/0096	.008	.015	.184
22	6	7/0096	.008	.015	.170
22	5	7/0096	.008	.015	.155
22	4	7/0096	.008	.015	.142
22	3	7/0096	.008	.015	.130
22	2	7/0096	.008	.015	.124

**Construction:**  
 Stranded bare copper conductors insulated with color coded PVC, jacketed with Gray PVC. Cables are twisted prior to jacketing. All cables are available with an overall aluminum/ polyester shield and a stranded tinned copper drain wire.



COLOR CODE: Black, Red White, Green, Orange, Blue, Brown, Yellow, Purple, Gray, Pink, Tan, Lt. Green, Lt. Blue, Lt. Orange, Lt. Purple.

Above cables also available as pairs or triads; unshielded, overall shielded, each group shielded

**504 Silver Street Manchester, NH 03103**  
**Phone (603) 624-2427 Fax (603) 641-9296**