

# BURTON

WIRE & CABLE

MANUFACTURER OF QUALITY WIRE & CABLE

## UNSHIELDED PLENUM FIRE ALARM CABLES

Gauge Size	No. of Conductors	Insulation Thickness	Jacket Thickness	Nominal O.D.
12	2	.010	0.015	0.232
14	2	.010	.015	0.198
14	4	.010	.015	0.233
16	2	.009	.015	0.168
16	4	.009	.015	0.196
18	2	.009	.015	0.147
18	4	.009	.015	0.171
18	6	.009	.015	0.205
18	8	.009	.015	0.223
18	10	.009	.015	0.263
22	4	.008	.015	0.130
22	6	.008	.015	0.154
22	8	.008	.015	0.167

### Construction:

**Solid bare copper conductors insulated with 75° Plenum Rated Red PVC. Cables are twisted prior to jacketing.**

COLOR CODE: Black, Red, Brown, Blue, Orange, Yellow, Purple, Green, White, Gray  
Flat cables are available in Red, Black, White, and Brown jacket colors.



**Power-Limited Fire-Alarm Cable  
(UL) Type FPLP, NEC Article 760**

**California State Fire Marshal Listed**



**504 Silver Street Manchester, NH 03103  
Phone (603) 624-2427 Fax (603) 641-9296**