

BURTON

WIRE & CABLE

SHIELDED PLENUM FIRE ALARM CABLES

MANUFACTURER OF QUALITY WIRE & CABLE

Gauge Size	No. of Conductors	Insulation Thickness	Jacket Thickness	Nominal O.D.
12	2	.010	.015	.236
14	2	.010	.015	.200
14	4	.010	.015	.237
16	2	.009	.015	.172
16	4	.009	.015	.202
18	2	.009	.015	.150
18	4	.009	.015	.174
18	6	.009	.015	.208
18	8	.009	.015	.227
18	10	.009	.015	.266
22	4	.008	.015	.133
22	6	.008	.015	.158
22	8	.008	.015	.172

Construction:
 Solid bare copper conductors insulated with 75° Plenum Rated Red PVC. Cables are twisted prior to jacketing. All cables are available with an overall aluminum / polyester shield and drain wire. FPLP OR CL3P

COLOR CODE: Black, Red, Brown, Blue, Orange, Yellow, Purple, Green, White, Gray
 Flat cables are available in Red, Black, White, and Brown jacket colors.



Power-Limited Fire-Alarm Cable
 (UL) Type FPLP, NEC Article 760

California State Fire Marshal Listed



504 Silver Street Manchester, NH 03103
 Phone (603) 624-2427 Fax (603) 641-9296